

### AMENDMENTS TO CLAIMS

- Please amend claims 9 and 20.
- Please add new claims 61-68 as indicated below. A complete listing of all claims and their status in the application are as follows:

Claims 1-8 (canceled)

9. (currently amended) A Remote Test Unit (RTU), comprising:  
a logic circuitry adapted to emulate a central Digital Subscriber Line Modem (DSLAM-C) for testing customer premises equipment containing a remote Digital Subscriber Line Modem (DSLAM-R), the logic circuitry is further adapted to test an ISO/OSI layer connected to the DSLAM, the ISO/OSI layer is selected from the group consisting of a network layer, a transport layer, a session layer, a presentation layer and an application layer; and  
a Digital Subscriber Line Modem Central/Remote (DSLAM-C/R) test head connected to the logic circuitry for connecting the logic circuitry to the DSLAM-R.
10. (original) The Remote Test Unit of claim 9 wherein:  
the logic circuitry is further adapted to emulate a DSLAM-R for testing central offices equipment including a Digital Subscriber Line Access Multiplexer (DSLAM) containing a DSLAM-C; and  
the DSLAM-C/R test head connects the logic circuitry to the DSLAM-C.
11. (original) The Remote Test Unit of claim 9 further including:  
a copper loop testing (CLT) test head connected to the logic circuitry for connecting the logic circuitry to customer premises equipment; and wherein  
the logic circuitry is further adapted to perform copper loop testing on a first connection between the logic circuitry and the customer premises equipment.
12. (original) The Remote Test Unit of claim 11 further including:  
a plurality of test ports; and  
an internal matrix connected to the plurality of test ports for selectively connecting the DSLAM-C/R test head and the CLT test head to the plurality of test ports.

13. (original) The Remote Test Unit of claim 12 wherein:  
each of the plurality of test ports is connected to the DSLAM.
14. (original) The Remote Test Unit of claim 12 wherein:  
the DSLM-C/R test head is connected to a first one of the plurality of test ports and  
the CLT test head is connected to a second one of the plurality of test ports, the  
first one of the plurality of test ports being shorted to the second one of the  
plurality of test ports.
15. (original) The Remote Test Unit of claim 9 wherein:  
the logic circuitry is further adapted to emulate a concentrator connected to the  
DSLAM.
16. (original) The Remote Test Unit of claim 15 wherein:  
the logic circuitry is further adapted to emulate a router connected to the concentrator.
17. (original) The Remote Test Unit of claim 16 wherein:  
the logic circuitry is further adapted to emulate an Internet service provider (ISP)  
connected to the router.
18. (original) The Remote Test Unit of claim 16 wherein:  
the logic circuitry is further adapted to emulate a web site connected to the ISP over  
an Internet.
19. (canceled)
20. (currently amended) A Remote Test Unit (RTU), comprising:  
a logic circuitry adapted to emulate:
  - a central Digital Subscriber Line Modem (DSLAM-C) for testing customer  
premises equipment containing a remote Digital Subscriber Line  
Modem (DSLAM-R), the logic circuitry is further adapted to test an  
ISO/OSI layer connected to the DSLAM, the ISO/OSI layer is selected  
from the group consisting of a network layer, a transport layer, a  
session layer, a presentation layer and an application layer, and
  - a DSLAM-R for testing central offices equipment including a Digital Subscriber  
Line Access Multiplexer (DSLAM) containing a DSLAM-C;

a Digital Subscriber Line Modem Central/Remote (DSLAM-C/R) test head connected to the logic circuitry for connecting the logic circuitry to the DSLAM-R and for connecting the logic circuitry to the DSLAM-C;  
a copper loop testing (CLT) test head connected to the logic circuitry for connecting the logic circuitry to the customer premises equipment; and wherein:  
the logic circuitry is further adapted to perform copper loop testing on a first connection between the logic circuitry and the customer premises equipment;  
a plurality of test ports; and  
an internal matrix connected to the plurality of test ports for selectively connecting the DSLAM-C/R test head and the CLT test head to the plurality of test ports.

21. (original) The Remote Test Unit of claim 20 wherein:  
the logic circuitry is further adapted to emulate a device selected from the group consisting of: a concentrator connected to the DSLAM, a router connected to the concentrator, an internet service provider (ISP) connected to the router, and a web site connected to the ISP over an Internet.
22. (canceled)
23. (previously presented) A network, comprising:  
a plurality of customer premises equipment, each of the plurality of customer premises equipment containing a remote Digital Subscriber Line Modem (DSLAM-R);  
central offices equipment including a Digital Subscriber Line Access Multiplexer (DSLAM) containing a central Digital Subscriber Line Modem (DSLAM-C);  
a remote test unit (RTU), the RTU including:  
a logic circuitry adapted to emulate the DSLAM-C for testing the DSLAM-R of the plurality of customer premises equipment, the logic circuitry is further adapted to test an ISO/OSI layer connected to the DSLAM, the ISO/OSI layer is selected from the group consisting of a network layer, a transport layer, a session layer, a presentation layer and an application layer, and

- a Digital Subscriber Line Modem Central/Remote (DSLAM-C/R) test head  
connected to the logic circuitry for connecting the logic circuitry to the  
DSLAM-R; and  
an access matrix adapted to selectively connect:  
the plurality of customer premises equipment to the DSLAM,  
the plurality of customer premises equipment to the RTU, and  
the DSLAM to the RTU.
24. (original) The network of claim 23 wherein:  
the logic circuitry is further adapted to emulate the DSLAM-R for testing the DSLAM-C;  
and  
the DSLAM-C/R test head connects the logic circuitry to the DSLAM-C.
25. (original) The network of claim 24, wherein the RTU further includes:  
a copper loop testing (CLT) test head connected to the logic circuitry for connecting  
the logic circuitry to customer premises equipment; and wherein  
the logic circuitry is further adapted to perform copper loop testing on a first  
connection between the logic circuitry and the customer premises equipment.
26. (original) The network of claim 25, wherein the RTU further includes:  
a plurality of test ports; and  
an internal matrix connected to the plurality of test ports for selectively connecting the  
DSLAM-C/R test head and the CLT test head to the plurality of test ports.
27. (original) The network of claim 26, wherein:  
each of the plurality of test ports is connected to the DSLAM.
28. (original) The network of claim 25, wherein:  
the DSLAM-C/R test head is connected to a first one of the plurality of test ports and  
the CLT test head is connected to a second one of the plurality of test ports, the  
first one of the plurality of test ports being shorted to the second one of the  
plurality of test ports.
29. (original) The network of claim 28 further including:  
a concentrator connected to the DSLAM for combining signals from the DSLAM into  
combined signals; and wherein:

the logic circuitry is further adapted to emulate the concentrator.

30. (original) The network of claim 23 further including:  
a router connected to the concentrator for routing the combined signals from the  
concentrator; and wherein:  
the logic circuitry is further adapted to emulate the router.
31. (original) The network of claim 23 further including:  
an Internet service provider connected to the router for receiving the combined signals  
and providing access to an Internet; and wherein:  
the logic circuitry is further adapted to emulate the ISP.
32. (original) The network of claim 23 further including:  
a web site connected to the ISP over the Internet; and wherein  
the logic circuitry is further adapted to emulate a web site connected to the ISP over  
the Internet.
33. (canceled)
34. (original) The network of claim 23 wherein:  
the access matrix is further adapted to selectively connect:  
one of the plurality of customer premises equipment to the RTU and block the  
one of plurality of customer premises equipment from the DSLAM;  
and  
the DSLAM to the RTU and block the DSLAM from the plurality of customer  
premises equipment.
35. (previously presented) A network, comprising:  
a plurality of customer premises equipment, each of the plurality of customer premises  
equipment containing a remote Digital Subscriber Line Modem (DSL-M-R);  
central offices equipment including a Digital Subscriber Line Access Multiplexer  
(DSL-M-C) containing a central Digital Subscriber Line Modem (DSL-M-C);  
a remote test unit (RTU), the RTU including:  
a logic circuitry adapted to emulate:  
the DSL-M-C for testing the DSL-M-R, and  
the DSL-M-R for the DSL-M-C,

the logic circuitry is further adapted to test an ISO/OSI layer connected to the DSLAM, the ISO/OSI layer is selected from the group consisting of a network layer, a transport layer, a session layer, a presentation layer and an application layer,

a Digital Subscriber Line Modem Central/Remote (DSLAM-C/R) test head connected to the logic circuitry for connecting the logic circuitry to the DSLAM-R and for connecting the logic circuitry to the DSLAM-C,

a copper loop testing (CLT) test head connected to the logic circuitry for connecting the logic circuitry to the customer premises equipment; and wherein:

the logic circuitry is further adapted to perform copper loop testing on a first connection between the logic circuitry and the customer premises equipment,

a plurality of test ports, and

an internal matrix connected to the plurality of test ports for selectively connecting the DSLAM-C/R test head and the CLT test head to the plurality of test ports, and

an access matrix adapted to selectively connect:

the plurality of customer premises equipment to the DSLAM,  
the plurality of customer premises equipment to the RTU, and  
the DSLAM to the RTU.

36. (original) The network of claim 35 further including:

a concentrator connected to the DSLAM for combining signals from the DSLAM into combined signals;

a router connected to the concentrator for routing the combined signals from the concentrator;

an Internet service provider connected to the router for receiving the combined signals and providing access to an Internet; and

a web site connected to the ISP over the Internet; and wherein:

the logic circuitry is further adapted to emulate the concentrator, the router, the ISP, and the web site.

37. (canceled)

38. (original) The network of claim 35 wherein:  
the access matrix is further adapted to selectively connect:  
one of the plurality of customer premises equipment to the RTU and block the  
one of plurality of customer premises equipment from the DSLAM;  
and  
the DSLAM to the RTU and block the DSLAM from the plurality of customer  
premises equipment.
39. (previously presented) A method for testing a network, comprising:  
emulating a central Digital Subscriber Line Modem (DSLAM-C);  
connecting the emulated DSLAM-C to an access matrix for testing customer premises  
equipment containing a remote Digital Subscriber Line Modem (DSLAM-R);  
and  
testing, using emulation, an ISO/OSI layer connected to the DSLAM, the ISO/OSI  
layer is selected from the group consisting of a network layer, a transport layer,  
a session layer, a presentation layer and an application layer.
40. (original) The method of claim 39 further including:  
emulating the DSLAM-R; and  
connecting the emulated DSLAM-R to the access matrix for testing central offices  
equipment including a Digital Subscriber Line Access Multiplexer (DSLAM)  
containing the DSLAM-C.
41. (original) The method of claim 40 further including:  
performing a copper loop testing (CLT) on a connection between the customer  
premises equipment and the central offices equipment.
42. (original) The method of claim 40 wherein:  
the step of connecting the emulated DSLAM-C to an access matrix further includes the  
step of connecting the emulated DSLAM-C to a first one of a plurality of test  
ports; and  
the step of connecting the emulated DSLAM-R to an access matrix further includes the  
step of connecting the emulated DSLAM-R to the first one of the plurality of  
test ports; and

the step of performing a CLT on a connection between the customer premises equipment and the central offices equipment further including the step of connecting the central offices equipment to a second one of the plurality of test ports.

43. (original) The method of claim 42 wherein:  
each of the plurality of test ports is connected to the DSLAM.
44. (original) The method of claim 42 wherein:  
the first one of the plurality of test ports and the second one of the plurality of test ports are shorted.
45. (original) The method of claim 39 further including:  
emulating a concentrator connected to the DSLAM.
46. (original) The method of claim 45 further including:  
emulating a router connected to the concentrator.
47. (original) The method of claim 46 further including:  
emulating an Internet service provider (ISP) connected to the router.
48. (original) The method of claim 46 further including:  
emulating a web site connected to the ISP over an Internet.
49. (canceled)
50. (original) The method of claim 40 wherein:  
the step of connecting the emulated DSLM-C to an access matrix for testing the customer premises equipment blocks the customer premises equipment from the central offices equipment.
51. (original) The method of claim 40 wherein:  
the step of connecting the emulated DSLM-R to an access matrix for testing the central offices equipment blocks the central offices equipment from the customer premises equipment.
52. (previously presented) A method for testing a network, comprising:  
emulating a central Digital Subscriber Line Modem (DSLM-C);



connecting the emulated DSLM-C to an access matrix for testing customer premises equipment containing a remote Digital Subscriber Line Modem (DSLAM-R);  
emulating the DSLAM-R;  
connecting the emulated DSLAM-R to the access matrix for testing central offices equipment including a Digital Subscriber Line Access Multiplexer (DSLAM) containing the DSLAM-C;  
performing a copper loop testing (CLT) on a connection between the customer premises equipment and the central offices equipment; and  
testing, using emulation, an ISO/OSI layer connected to the DSLAM, the ISO/OSI layer is selected from the group consisting of a network layer, a transport layer, a session layer, a presentation layer and an application layer.

53. (original) The method of claim 52 wherein:  
the step of connecting the emulated DSLAM-C to an access matrix further includes the step of connecting the emulated DSLAM-C to a first one of a plurality of test ports; and  
the step of connecting the emulated DSLAM-R to an access matrix further includes the step of connecting the emulated DSLAM-R to a second one of the plurality of test ports; and  
the step of performing a CLT on a connection between the customer premises equipment and the central offices equipment further including the step of connecting the central offices equipment to a third one of the plurality of test ports.
54. (original) The method of claim 53 wherein:  
the first one of the plurality of test ports, the second one of the plurality of test ports, and the third plurality of test ports are shorted.
55. (original) The method of claim 52 further including:  
emulating a concentrator connected to the DSLAM.
56. (original) The method of claim 55 further including:  
emulating a router connected to the concentrator.
57. (original) The method of claim 56 further including:  
emulating an Internet service provider (ISP) connected to the router.

58. (original) The method of claim 57 further including:  
emulating a web site connected to the ISP over an Internet.
59. (canceled)
60. (original) The method of claim 52 wherein:  
the step of connecting the emulated DSLM-C to an access matrix for testing the  
customer premises equipment blocks the customer premises equipment from  
the central offices equipment; and  
the step of connecting the emulated DSLM-R to an access matrix for testing the  
central offices equipment blocks the central offices equipment from the  
customer premises equipment.
61. (new) A Remote Test Unit (RTU), comprising:  
logic circuitry for emulating a central modem for testing customer premises equipment  
containing a remote modem; and  
a modem central/remote test head connected to the logic circuitry for connecting the  
logic circuitry to the remote modem.
62. (new) The Remote Test Unit of claim 61 wherein:  
the logic circuitry is further for emulating a remote modem for testing central offices  
equipment including a multiplexer containing a central modem; and  
the modem central/remote test head connects the logic circuitry to the central modem.
63. new) The Remote Test Unit of claim 61 further including:  
a copper loop testing (CLT) test head connected to the logic circuitry for connecting  
the logic circuitry to customer premises equipment; and wherein  
the logic circuitry is further for performing copper loop testing on a first connection  
between the logic circuitry and the customer premises equipment.
64. (new) The Remote Test Unit of claim 63 further including:  
a plurality of test ports; and  
an internal matrix connected to the plurality of test ports for selectively connecting the  
modem central/remote test head and the CLT test head to the plurality of test  
ports.

65. (new) The Remote Test Unit of claim 64 wherein:  
each of the plurality of test ports is connected to the multiplexer.
66. (new) The Remote Test Unit of claim 64 wherein:  
the modem central/remote test head is connected to a first one of the plurality of test ports and the CLT test head is connected to a second one of the plurality of test ports, the first one of the plurality of test ports for being shorted to the second one of the plurality of test ports.
67. (new) The Remote Test Unit of claim 61 wherein:  
the logic circuitry is further for emulating a concentrator connected to the multiplexer.
68. (new) The Remote Test Unit of claim 67 wherein:  
the logic circuitry is further for emulating a router connected to the concentrator.